PBInternational
Clean and safe water

Revision: 14-4-2021

# UFK

## Product information




## UFK filter

The UFK filter module is an independently operating filter and can easily be used as a gatekeeper in a small-scale pipeline network, a pipe section or an individual tapping point. The filter is suitable for cold water installations with a maximum temperature of 40° Celsius.

With the periodic forward flush, pollution is automatically flushed away. The automatic flushing of the filter combined with annual maintenance ensures a lifespan of 5 years.
The UFK has minimal management costs, annual thorough cleaning of the modules and settings check is sufficient.

| Art. nr. | Description | Capacity * | Dimensions HxWxD (cm) |
|---|---|---|---|
| 1105050510 | UFK 50-510 | 0,3 m³/h | 90×30×12 |
| 1105063510 | UFK 63-510 | 0,5 m³/h | 92×32×13 |
| 1105075510 | UFK 75-510 | 0,7 m³/h | 95×33×14 |
| 1105090510 | UFK 90-510 | 1 m³/h | 96×32×15 |
| 1105090750 | UFK 90-750 | 1,5 m³/h | 116×32×15 |
| 1105090100 | UFK 90-1000 | 2 m³/h | 145×34×15 |
| 1105110750 | UFK 110-750 | 2 m³/h | 123×35×16 |
| 1105125750 | UFK 125-750 | 2,5 m³/h | 124×36×17 |
| 1105140750 | UFK 140-750 | 3 m³/h | 126×37×19 |
| 1105160750 | UFK 160-750 | 4 m³/h | 127×38×20 |
| 1105160100 | UFK 160-1000 | 5 m³/h | 156×38×20 |

** For drinking water at 16° C and water pressure of 2 bar.*

| Delivered inclusive: | |
|---|---|
| ✓ Drain valve and timer | ✓ Pre filter |
| ✓ Connection bij three-part coupling | ✓ Non return valve |
| ✓ Manual valves | ✓ Pipe clambs |
| ✓ Manometers | ✓ Power cord (2m) |

- Long-term solution against legionella norm overruns.
- Includes flushing set and suitable mounting materials.
- Applications: Shower legionella prevention, pre-filter Reverse osmosis, general water filter.